

LUCCA

Kleurenkaart



LUCCA

Kleurenkaart



LUCCA

Kleurenkaart



LUCCA

Kleurenkaart



LUCCA

Kleurenkaart



LUCCA

Kleurenkaart




LUCCA

Kleurenkaart



HUISLIJN

LUCCA COLLECTION

<p>General Product Specifications</p> <p>Quality Name : MESSINA-B5 Design Name : MESSINA 88 Composition : %66 PAN %34 PES</p> <p>Useable width (±2 cm) : 140 cm / 55 "</p> <p>Weight : 690 gr/m MOQ : mt.</p>	<p>Production Category Suitable for</p> <p><input type="checkbox"/> Plain weave <input checked="" type="checkbox"/> Upholstery <input checked="" type="checkbox"/> Jacquard weave <input checked="" type="checkbox"/> Light upholstery <input type="checkbox"/> Knitted <input type="checkbox"/> Curtains/draperies</p> <p>Dye Method</p> <p><input type="checkbox"/> Piece dyed <input type="checkbox"/> IMO -Marine <input checked="" type="checkbox"/> Yarn dyed <input checked="" type="checkbox"/> Bed covering <input type="checkbox"/> Printed <input type="checkbox"/> Contract upholstery for ASTM D 4157</p>																																								
<p>Care codes</p> <p>Washable : Wash 30°C gentle cycle Iron : Low iron at max 110°C Tumble dry : Do not tumble dry Bleach : Do not bleach Dry clean P : Dry-cleaning in perchloroethylene gentle cycle</p> <p></p>	<p>FR Standards</p> <p>BS 5852:2006 Source 0-Cigarette Test : PASS BS 5852 Crib 5 : EN 1021-1 Cigarette Test : PASS CAL 117 : COMPLIES NFPA 260/UFAC : CLASS I NFPA 701 : NF P92-507 :</p>																																								
<p>Test Specifications</p> <table border="0"> <tr> <td>Abrasion Resistance (Martindale) ISO 12947-2</td> <td>45,000</td> <td>rubs</td> <td></td> </tr> <tr> <td>Abrasion Resistance (Wyzenbeek) ASTM D4157-13</td> <td></td> <td>double rubs</td> <td></td> </tr> <tr> <td>Pilling ISO 12945-2 (2.000 Cycles)</td> <td>4/5</td> <td></td> <td></td> </tr> <tr> <td>Brush Pilling (D3511-99A)</td> <td>4/5</td> <td></td> <td></td> </tr> <tr> <td>Colour fastness to rubbing: ISO 105-X12</td> <td>: Dry --- 4</td> <td></td> <td>Wet ---> 3/4</td> </tr> <tr> <td>Colour fastness to light: ISO 105-B02</td> <td>:</td> <td></td> <td></td> </tr> <tr> <td>Tearing strength: ISO 13937-3</td> <td>: Warp --></td> <td>N</td> <td>Weft --> N</td> </tr> <tr> <td>Tensile strength: ISO 13934-1</td> <td>: Warp --></td> <td>N</td> <td>Weft --> N</td> </tr> <tr> <td>Elongation: ISO 13934-1</td> <td>: Warp --></td> <td>%</td> <td>Weft --> %</td> </tr> <tr> <td>Seam slippage: ISO 13936-2</td> <td>: Warp --> 3,0</td> <td>mm</td> <td>Weft --> 3,5 mm</td> </tr> </table>		Abrasion Resistance (Martindale) ISO 12947-2	45,000	rubs		Abrasion Resistance (Wyzenbeek) ASTM D4157-13		double rubs		Pilling ISO 12945-2 (2.000 Cycles)	4/5			Brush Pilling (D3511-99A)	4/5			Colour fastness to rubbing: ISO 105-X12	: Dry --- 4		Wet ---> 3/4	Colour fastness to light: ISO 105-B02	:			Tearing strength: ISO 13937-3	: Warp -->	N	Weft --> N	Tensile strength: ISO 13934-1	: Warp -->	N	Weft --> N	Elongation: ISO 13934-1	: Warp -->	%	Weft --> %	Seam slippage: ISO 13936-2	: Warp --> 3,0	mm	Weft --> 3,5 mm
Abrasion Resistance (Martindale) ISO 12947-2	45,000	rubs																																							
Abrasion Resistance (Wyzenbeek) ASTM D4157-13		double rubs																																							
Pilling ISO 12945-2 (2.000 Cycles)	4/5																																								
Brush Pilling (D3511-99A)	4/5																																								
Colour fastness to rubbing: ISO 105-X12	: Dry --- 4		Wet ---> 3/4																																						
Colour fastness to light: ISO 105-B02	:																																								
Tearing strength: ISO 13937-3	: Warp -->	N	Weft --> N																																						
Tensile strength: ISO 13934-1	: Warp -->	N	Weft --> N																																						
Elongation: ISO 13934-1	: Warp -->	%	Weft --> %																																						
Seam slippage: ISO 13936-2	: Warp --> 3,0	mm	Weft --> 3,5 mm																																						

Our products fulfil the requirements of Annex XVII of REACH (incl. the use of azo-dyes, heavy metals, etc.) as well as the American requirement regarding total content of lead in children's articles)
 In stain repellent products, we always use human and environmental friendly C6 fluorocarbons. In FR treatment, we always use DecaBDE free FR compounds.
 The colours in production might slightly vary from this reference due to different lots in production.



SUSTAINABLE TEXTILES